

MARUNAKA BL25mini4

4-STROKE POWERED HANDHELD BLOWER



CLEAN EXHAUST EMISSION AND LOW FUEL CONSUMPTION

In order to conform to US CARB(Tire2),EPA(Phase2)and EIRO regulations. We have introduced the clean emission Robin Powered handheld blower with Robin Micro 4-stroke over head valve engine model EH025(24.5ml).

COMPACT AND LIGHT WEIGHT

Lightest in weight in this class. Compact and light weight Robin MICRO 4-STROKE Engine.

EASY STARTING AND HANDLING

Mechanical decompression system for easy Recoil pulling. Use regular automobile gasoline.No need to mix 2-cycle engine oil and gasoline.

Exhaust Emission □HC+Nox

EPA Phase II (2005)Regulation	BL25mini4
Europe Stage II (2007)	
50g/kWH	24g/kWH

Meet all EPA, CARB and EURO Emission standards

One unit for dual purposes



■BL25mini4 [BLOWER ONLY]

- Weight:4.4kg(9.8lbs)
- Dimensions:(W)221 × (H)368mm



■BL25mini4 [BLOWER&VACUUM]

- Weight:4.5kg(10.1lbs)
- Dimensions:(W)231 × (H)368mm

Engine Type	Displacement	Carburetor	Tank Capacity	Maximum Air Volume (with optional flat nozzle)	Maximum Air Speed	Noise	Operation Hours
4-STROKE OHV	24.5ml	DIAPHRAGM	520ml 17.7floz(USA)	10.1m ³ /min (358cf/m)	64.6m/sec (145MPH)	66.5dB(A)	60min

※The specification is subject to change without notice for the purpose of improvement of the product.

BL25 mini4

4-STROKE POWERED HANDHELD BLOWER

BLOWER & VACUUM



**Take the hard work out of clearing leaves and garden debris.
Make these tiresome tasks quick and easy.**

8.9m³/min MAXIMUM AIR VOLUME WITH STANDARD ROUND NOZZLE. 10.1m³/min WITH OPTIONAL FLAT NOZZLE.

Impeller is mounted directly on to the flywheel so that to reduce total width. 15mm shorter than FL260. 3mm Larger (compared with FL260) impeller gives more Air Volume. Circle cross section design Volute Case for high efficiency and less Air noise.



FUNCTIONAL DESIGN AND HIGH BLOWER PERFORMANCE



Operator can fix machine power steplessly with "Cruise Control" on the "Thumb Control Lever." "Thumb Control Lever" for easy handling of the blower. Professional Rubber Grip for greater comfort.



Handle Grip for vacuum Attachment is part of the Fuel Tank. Simple unified design and easy to handle

FUNCTIONAL DESIGN AND HIGH BLOWER PERFORMANCE



Sliding "Plug Cover." Easy to maintain and no way of missing.

Check Spark plug if it's dirty or not. Electrode gap should be between 0.7 and 0.8mm.



Extended Oil Drain Plug. Easy to change Oil. Fill 80ml oil up to the bottom of Oil Inlet (Stop adding oil when you see the oil at the bottom of the oil Inlet.) Do not fill oil up to the mouth of the Oil Inlet.